

Used machines offer

MT750 1214014 - Aebi MT750 EU6 85km/h 7,5t 4x4

Offer number: UM3436488

aebi schmidt
group



Brand: Aebi
 Mat.-Nr.: 1222119-7
 Year of manufacture: 2017
 Serialnumber: TAH31100EG1214014
 Running hours: 2,200 h
 Mileage: 5,500 km
 Condition: Class 4
 Location: Norway
 4993 Sundebru

Price: **On request**

The offered a package of machines ready for work:

- MT 750 4X4 Euro 6 Speed limit 85 km/h, 7.5 t (appr. 5.500 km / 2.200 hrs)
- Syntos B 15L-21 E
- Watertank with parking-legs
- Washer RPS-H
- Washing equipment

Gallery



Type utstyr	Varenummer
Aebi MT 750 Euro6	1222119-7
SYNTOS B 15L-21 E	1148826-8
Stolpe- og autovernvasker RPS-H	1056933-3
Spyleanlegg Tøllefsdal	1243472-4
Vanntank med p.bein og høytrykkspumpe	1344743-3

Equipment

Aebi | MT750 | 2017

P1222119-7	Aebi MT750, EU6, 156HP, 6 cylinder
Speed/Traction	
P1191232-6	MT750 Speed limit 85 km/h 7.5 t
P1194992-0	MT750 4x4 operation, Operation on front axle can be switched on/off
PM7-V01/3	Selectable 4x4 operation
PM7-V01/11	Differential lock rear axle MT740 4x4
PM7-NB/2	Differential lock front and rear axle
Wheelbase/suspension	
P1190246-2	MT750 Wheelbase 2750 mm
P1219786-5	Single wheels on rear axle, standard suspension
Seat	
PM7-K07/3	Comfort seat with automatic pneumatic adjustment for the driver
PM7-K06/1	Single seat for passenger, adjustable and sprung
Wheels	
PM7-R28	245/70 R 17.5 (143/141J) 17.5 x 6.75 SINGLE
Driver Cab	
P1190853-6	MT740 6,750 White RAL 9010
PM7-K04/9	Air conditioning
PM7-K09/7	Heated side mirrors
PM7-K12/3	Digital tachograph Siemens VDO, mandated in the EU
PM7-K24	Central locking via key
PM7-E01/1	3-pole connector for break light
PM7-K03/4	Heated windscreen
PM7-K20/2	Break light beam with 4 lamps and rotating warning light
PM7-E03/1	13-pin connector for equipment and trailer
Hydraulics	
PM7-H32	3 circuit hydraulics prop. maneuver 30 l & working hydraulics w/ leak, 50 l 180 bar
PM7-H38	1st extra valve h. front for maneuver hydraulics, DBV (PM7-H30, PM7-H31 or PM7-H32)
PM7-H39	Hyd.coll. rear right for maneuver hydraulic, DBV, from extra valve f. right (PM7-H38)
PM7-H40	2nd extra valve v. front for man.hydr. DBV (PM7-H30 or PM7-H31 or PM7-H32)
PM7-H34/1	Continuous quantity on circuit 1 with 30l 250 bar, requires H30 or H31 or H32
Other	
PM7-E04/1	Main power switch on battery
PM7-K23/2	Work light on a stand on the back wall of the cabin
PM7-A30	Front plate DIN B (Size 3)
PM7-14/11	Automatic trailer coupling, rear traverse and compressed air brakes
Box	
PM7-A07	3-way plane with tip 2950x1700x400 mm compl. in aluminum for wheel distance 2750mm
PM7-A25	Elevation in aluminum or steel of front limb on tipping plane
Customer Specific Options (SSR)	
P1250651-2	Extra rust protection
P1239476-8	Winter package for 6 cylinder engine (clutch booster & alternator 180A)
P1229917-6	Heating down to the floor
Spreader Schmidt SYNTOSB 15L-21 E 1,5m3 2017	
662724	Spreader SYNTOS B 15L (21), hopper from plastic
Minimum mounting length	2600mm.
Needed cargo length	3,55m.
Empty weight	506 kg.
Center of gravity	aprox.597 from frontside hopper
	Full loaded platform height 950mm
Hopper	
136900	Frame extension + 300 mm (24) (SYNTOS B 11L, 15L)
193450	Belt conveyer system („B“)

667646	Hopper screen 40x40mm, steel (for SYNTOS B 08K - 15L)
575726	Cover (for SYNTOS 08K - 15L)
851444	Hopper in orange (RAL2011) (SYNTOS)
763893	Gravity point centering flap inside in hopper
Pre-wet system	
777409	Pre-wet system SYNTOS
171572	Pre-wet system EN15597-1 min. & max. level & scale for liquid le
912321	Pre-wet coupling Storz 2"
388150	Maximum level switch 4P (part of 171572)
536469	Minimum level switch (part of 171572)
	Turning off brine pump running dry Yes
Drive system	
474903	Drive system via vehicle hydraulics („V“)
252518	Hydr. couplings not leak free, ISO7241-1 Serie“A“ P=Sz12.5(M) R=S
Control system	
968675	Control system Evolution Smart „ES“, with colour touchscreen
515636	RS232/plough signal Interface (with 19-Pole control box cable EP/
423554	Cable extension (cabin wall connector), standard version
605088	Control box support, RAM mount compatible
	A Special units for program operating system International metric (wid dos.=gr/m2)
Distribution system	
591112	Spreading disc „350“ (2 - 6 metres)
143517	Infrared spreading control (for EC, EP and ES)
438459	Rear working lamp, LED light, for spreading control
	Rear work light colour Red working light
Demount and fixing	
198579	Mounting frame for demount legs (for 3.5T demounting)
621273	Painted mounting frame, RAL7021
833280	Demounting legs (4 pc.) 1.4 t. capacity, spindle in middle (for K
361512	Adjustable sidebars, 4 pc. (for 06K-17KR)
487836	Securing belts, 4 items, 1200daN (according EN12195-2 and VDI2702
Options	
919749	Beacon 1 pc. with LED light, orange
407687	Rear light
522948	Rear axle protection, splash screen 1.500 mm
Additional features	
	- from loading platform,, 597 mm.
Sprayer Schmidt CSP1600 2017	
1344743-3	Water tank MT (CSP) 1600 liters w/valve bulkhead, quantity indicator, filling frame w/filter and cover with rotating lamp
1132756-6	Parking legs, 3 t load capacity, w/ manual crank
99999-8	Hydraulically driven high-pressure washer w/hose drum and lance
99999-9	Arrangement for water supply for washing brush
Schmidt Washer RPS-H 2017	
	1111111
Schmidt Washing equipment 2017	
	1111111

Contact

Arne Cato Snarvold

Phone: +47 90 85 91 31

E-Mail: arne.cato.snarvold@aebi-schmidt.com



© Aebi Schmidt Group | www.aebi-schmidt.com

Aebi Schmidt Holding AG | CH-8050 Zurich, Switzerland

All rights reserved. Technical data is subject to change.
Illustrations are not binding. Errors and amendments excepted.

 **aebi schmidt**
group

Document created on
2 SEP 2024